

Liquid Receivers



SKY Part No.	Connection	Height	Diameter	Volume
309-14	3/4 R/L x 1/4 ID (Top outlet)	200	100	1.4L
309-24	3/4 R/L x 3/8 ID (Top outlet)	272	114	2.4L
309-44	3/4 R/L x 1/2 ID (Top outlet)	332	165	5.1L
309-82	1 R/L x 1 R/L	449	165	8.2L
309-100	1 R/L x 1 R/L	510	165	10L
309-109	1 R/L x 1 R/L	354	219	11L
309-145	1 R/L x 1 R/L	434	219	14.6L
309-245	1 3/4 R/L X 1 3/4 R/L (Top outlet)	546	273	24.5L
309-35-V	1 1/4 R/L x 1/3/4 R/L	1000	219	35L
309-45-V	1 3/4 R/L X 1 3/4 R/L	900	273	45L
309-60-V	1 3/4 R/L X 1 3/4 R/L	1200	273	60L
309-90-V	2 1/4 R/L x 2 1/4 R/L	1233	325	90L
	Horizontal			
309-35-H	1 1/4 R/L x 1/3/4 R/L	1000	219	35L
309-45-H	1 3/4 R/L X 1 3/4 R/L	900	273	45L
309-60-H	1 3/4 R/L X 1 3/4 R/L	1200	273	60L
309-125-H	1 5/8 Cast iron valve's	1146	400	125L
	Horizontal and Vertical			
309-100-VH	2 1/4 R/L X 2 1/4 R/L	1440	232	100L
309-130-VH	1 5/8 Cast iron valve's	1191	400	130L
309-160-VH	1 5/8 Cast iron valve's	1434	400	160L
309-200-VH	2 1/8 Cast iron valve's	1200	485	200L
309-250-VH	2 1/8 Cast iron valve's	1500	485	250L

Manufactured in accordance with ISO 5149.2, with a SWP of 3,300 kpa

- ✳️ Featuring minimal pd to improve your plants efficiency.
- ✳️ Where fitted with a PRV socket, a SKY safety socket is used to ensure nil chance of refrigerant leakage.
- ✳️ Anti-corrosion powder coat finish with solid copper connections.
- ✳️ Receivers supplied without valves
- ✳️ Large vertical receivers have liquid level switch port

Discharge Muffler and Harmonic Attenuators



Sky no:	Connection	lay in	Dia	SWP
311-14	7/8" ID	280mm	76mm	4200kpa
311-18	1 1/8" ID	310mm	76mm	3600kpa
311-22	1 3/8" ID	350mm	102mm	3600kpa
311-26	1 5/8" ID	360mm	102mm	3600kpa
311-32	2 1/8" ID	546mm	152mm	3600kpa

- ✳️ Utilizing harmonic wave cut principles to reduce noise and smooth the discharge pulse.
- ✳️ Oil drain channels (no oil logging)
- ✳️ Solid copper connectors.



Custom made pressure vessels on request