


RANCO Reversing Valves (High Pressure R-410A)

- ❄ Developed for use with R-410A and R22
- ❄ Safe working pressure 4,200kpa
- ❄ Wide operating range of -30° - 130°C
- ❄ Certified UL ,VDE, CQC



SKY Part No.	Capacity R-22/407C		Connections	
	Kw	Tons	D	E/S/C
SHF-4H-23U-P	4.5	1.25	5/16	3/8
SHF-7H-34U-P	11.1	2	3/8	1/2
SHF-9H-35U-P	11.5	2.5	3/8	5/8
SHF-11H-45D1	11.5	3.1	1/2	5/8
SHF-20A-46	15.6	5.6	1/2	3/4
SHF-20A-47	15.6	5.6	1/2	7/8
SHF-20D-57	16	5.6	5/8	7/8
SHF-35A-67	20	10	3/4	7/8
SHF-35A-79	20	10	7/8	1 1/8
SHF-50-911D2	41	12	1 1/8	1 3/8

Reversing Valve Coils

SKY Part No.	Voltage	Connection
SHF-4-10FA5	240Vac	Spade
SHF-4-10FA4	24Vac	Spade
SHF-4-10L3	240V	Lead Wire
SHF-4-10L5	24V	Lead Wire

Competitor cross reference

SKY Part No.	RAN	SAG
SHF-4H-23U-P		STF-0101G
SHF-7H-34U-P	V2-408064-2IL	STF-0202G
SHF-9H-35U-P		STF-0301G
SHF-11H-45D1	V3-410084-7IL	STF-0310G
SHF-20A-46	V6-412084-1IL	STF-0408G
SHF-20A-47	V6-414084-1IL	STF-0409G
SHF-35A-67	V10-414124-2IL	STF-0101G
SHF-35A-79	V10-418144-2IL	STF-00720G
SHF-50-911D2	V124-220-T4210	
SHF-4-10FA5	LDL-41	
SHF-4-10FA4	LDL-41	

