

# Liquid & Moisture Indicating Sight Glass



- ❄ Fast and Accurate Tri-Range Moisture Indicator
- ❄ Wide viewing angle
- ❄ Solid Copper connectors for ease of installation
- ❄ Hermetically Sealed
- ❄ R-410A compatible, 48bar SWP

Manufactured in accordance with AS1677.2



**Sight Glass Solder Connection**



SKY Part No.	Item Description	Lay-in Length
605-0404	1/4" Sol	132
605-0606	3/8" Sol	132
605-0808	1/2" Sol	132
605-1010	5/8" Sol	132
605-1212	3/4 Sol	145




**Sight Glass Male Flare x Female Flare**

SKY Part No.	Item Description	Lay-in Length
603-0404	1/4"	62mm
603-0606	3/8"	76mm
603-0808	1/2"	72mm



**Sight Glass Flare**

SKY Part No.	Item Description	Lay-in Length
600-0404	1/4" Flare	70mm
600-0606	3/8" Flare	76mm
600-0808	1/2" Flare	83mm
600-1010	5/8" Flare	88mm



**Copper Body Single Glass**



SKY Part No.	Item Description	Lay-in Length
607-1414	Copper Body - 7/8" Sol	160
607-1818	Copper Body - 1 1/8" Sol	160
607-2222	Copper Body - 1 3/8" Sol	200
607-2626	Copper Body - 1 5/8" Sol	200
607-3434	Copper Body - 2 1/8" Sol	200



**Sight Glass Male Flare x Female Flare Swivel**

SKY Part No.	Item Description	Lay-in Length
608-0404	1/4"	82mm
608-0606	3/8"	87mm
608-0808	1/2"	94mm
608-1010	5/8"	105mm



**Additional Sight Glasses**

SKY Part No.	Item Description
608-20B	1-1/4 Rotalock Sight Glass with indicator ball
608-21	1-1/4 Rotalock Sight Glass
608-21 K	1-1/4 Rotalock Sight Glass c/w weld socket
610-12	3/4 NPT Fused Glass
610-16	1 NPT Fused Glass
610-20	1- 1/4 NPT Fused Glass
610-24	1 1/2 NPT Fused Glass
610-21	2" NPT Fused Glass
611-14	Sight Glass Assembly 7/8 to 1 1/8 tube

## Liquid Level Switch (Westermeyer)



Sky no:	Conection	Voltage	Contact	Amp	Fluid temp
LS-240	1/2 NPT	240V	N/C	0.25	-40 to 90°C
LS-240A	1/2 NPT	240V	N/O	0.25	-40 to 90°C

- ❄ Hermetically sealed with non invasive servicing
- ❄ Can be used to sense both refrigerant and oil levels.
- ❄ 6900Kpa safe working pressure



Sky no:	Conection	Voltage	Contact	Amp	Fluid temp
LS-LC2	1 1/14 R/L	24V	N/C & N/O	5A	-10

- ❄ Both NO and NC contacts
- ❄ Able to retrofit to an R/L sight glass socket